



STATAMAT
BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem
Tel. 09-2555333 Fax 09-2555339
E-mail info@statamat.be
Web www.statamat.be

MORLEY IAS
FIRE SYSTEMS

by Honeywell



PART V

INTELLIGENT DETECTORS & DEVICES



STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem
Tel. 09-2555333 Fax 09-2555339
E-mail info@statamat.be
Web www.statamat.be

MORLEY IAS
FIRE SYSTEMS

by Honeywell

V - Analogue Detectors and Devices

Analogue Morley IAS Detectors

MI Series

The MI series is a range of intelligent detectors, which have been produced using the latest in manufacturing technology and supplied with an array of advanced features, making them 'better by design'.

The MI series is equipped with a micro controller that manages the analogue signal and transmits it to the panel by a digital signal.

The MI series is protected against electro magnetic ray by a aluminium screen and against humidity by a silicone membrane. A insect resistant screen protects the optical chamber. A removable cover allows a field cleaning. The reliability of the electrical contact is improved by soldering of contacts directly on board.



A Magnetic Test Unit can be used in conjunction with the MI series detectors for alarm test purposes.

The MI series detectors have 2 integral LED's, which illuminate to provide a local alarm signal. These latch on, and remain illuminated until the detector is reset. An optional remote LED annunciator may be used to repeat any alarm signal.

The individual address can be easily set and read, using 2 rotary decade address switches located on the rear of the detector.



LPCB & BOSEC approved to EN54

REFERENCE	Detectors	UNIT PRICE IN €
	The detector is delivered without base that has to be ordered separately.	
	The price in grey color will become valid from 01/01/10.	
MI-PSE	1W ANALOGUE OPTICAL DETECTOR Dimensions: diam. 102mm x h: 34mm + 9 mm (base)	63,60 71,40
MI-FHSE	1W ANALOGUE HEAT DETECTOR - 58°C Dimensions: diam. 102mm x h: 41mm + 9 mm (base)	57,20 64,50
MI-HTSE	1W ANALOGUE HEAT DETECTOR - 78°C Dimensions: diam. 102mm x h: 41mm + 9 mm (base)	57,20 64,50
MI-RHSE	1W ANALOGUE HEAT DETECTOR 78°C & RATE OF RISE Dimensions: diam. 102mm x h: 41mm + 9 mm (base)	57,20 64,50



STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem
 Tel. 09-2555333 Fax 09-2555339
 E-mail info@statamat.be
 Web www.statamat.be

MORLEY IAS
 FIRE SYSTEMS

by Honeywell

REFERENCE	Advanced Detectors	UNIT PRICE IN €
MI-PTSE	1W ANALOGUE MULTICRITERIA DETECTOR OPTICAL-THERMAL Dimensions: diam. 102mm x h: 34mm + 9 mm (base)	82,00 92,00
▼▼ NEW		
MI-PTIR	1W ANALOGUE MULTI CRITERIA DETECTOR OPTICAL-THERMAL - IR Dimensions: diam. 102mm x h: 55mm + 9 mm (base)	124,10 141,00
MI-LZR	1W ANALOGUE HIGH SENSITIVITY LASER DETECTOR High sensitive detector for early detection, Especially dedicated for computer rooms, white rooms, etc.. Dimensions: diam. 102mm x h: 34mm + 9 mm (base)	277,00

REFERENCE	Advanced Protocol MI200 AV Series	UNIT PRICE IN €
-----------	-----------------------------------	--------------------

▼▼ NEW

The MI200 AV series is a range of intelligent detectors, which has been designed to comply the most recent needs of the market:

- * High immunity against false alarm
- * Early activation
- * Repeatability for installation
- * Standard base for all detectors
- * Easy to maintain



OPTICAL AP DETECTOR



THERMAL & MULTI CRITERIA AP DETECTORS

The MI200 AV series is equipped with a micro controller that manages the analogue signal and transmits it to the panel by a NEW ADVANCED DIGITAL PROTOCOL. In addition of the standards features already available in the MI series, like the magnetic test control, the 2 integrated LED's, ... the MI200 AV series offers significant new

options:

- * New mechanical design to facilitate measures and limit drift
- * Bi-directional digital communication with the panel
- * Direct decade address 01-159 entry
- * Free control of the remote indicator output
- * Standard base for all detectors

LPCB approved EN54

BOSEC system approvals ongoing

AVAILABLE SOON !! (Q4-2009)

**STATAMAT**

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem



Tel. 09-2555333 Fax 09-2555339

E-mail info@statamat.be

Web www.statamat.be

MORLEY IAS
FIRE SYSTEMS

by Honeywell

REFERENCE	Detectors	UNIT PRICE IN €
	xx= color type __ = bright white IV = ivory	
	The detector is delivered without base that has to be ordered separately.	
MI-PSE-S2-xx 1W	ANALOGUE OPTICAL SENSOR ADV	63,60
MI-PSE-S2I-xx 1W	ANALOGUE OPTICAL SENSOR AVD ISOLATOR INCLUDED	69,50
MI-FHSE-S2-xx 1W	ANALOGUE 58°C THERM SENSOR AVD	57,20
MI-FHSE-S2I-xx 1W	ANALOGUE 58°C THERM SENSOR AVD ISOLATOR INCLUDED	63,10
MI-HTSE-S2-xx 1W	ANALOGUE 78°C THERM SENSOR AVD	57,20
MI-HTSE-S2I-xx 1W	ANALOGUE 78°C THERM SENSOR AVD ISOLATOR INCLUDED	63,10
MI-RHSE-S2-xx 1W	ANALOGUE R.O.R. THERM SENSOR AVD Alarms when temperature exceeds 58°C or 10°C/min.	57,20
MI-RHSE-S2I-xx 1W	ANALOGUE R.O.R. THERM SENSOR AVD ISOLATOR INCLUDED	63,10
MI-PTSE-S2-xx 1W	ANALOGUE MULTI (O/T) SENSOR AVD	82,00
MI-PTSE-S2I-xx 1W	ANALOGUE MULTI SENSOR AVD ISOLATOR INCLUDED	87,90
MI-PTIR-S2-xx 1W	ANALOGUE MULTI (O/T/IR) SENSOR AVD	124,10
MI-PTIR-S2I-xx 1W	ANALOGUE MULTI SENSOR AVD ISOLATOR INCLUDED	130,00



STATAMAT







BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem
Tel. 09-2555333 Fax 09-2555339
E-mail info@statamat.be
Web www.statamat.be

MORLEY IAS
FIRE SYSTEMS

by Honeywell

Detector Bases & Accessories

REFERENCE	Analogue Bases	UNIT PRICE IN €
▼▼ NEW		
B501AP-xx	1W ADVANCED PROTOCOL STANDARD MOUNTING BASE xx = color: __ : bright white; IV: ivory Address tag included and wide hole. Dimensions: diam. 102mm x (h) 21mm AVAILABLE SOON !!	 7,50
B501DG	1W DEEP MOUNTING BASE (26MM) SEMS screw connections and address identification label. PACKED PER 10	 10,50 12,50
B524IEFT-1	1W MOUNTING BASE WITH MOSFET ISOLATOR Deep analogue sensor base with FET isolator. SEMS screw connections and address identification label.	 12,50 14,40
	xx= color type WH = bright white IV = ivory	
B524HTR-xx	1W HEATED BASE Deep analogue sensor base with heater resistor. SEMS screw connections and address identification label.	 61,50
B524RTE-xx	1W MOUNTING BASE WITH RELAY Deep analogue sensor base with built in relay. SEMS screw connections and address identification label.	 52,50



STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem
Tel. 09-2555333 Fax 09-2555339
E-mail info@statamat.be
Web www.statamat.be

MORLEY IAS
FIRE SYSTEMS

by Honeywell

REFERENCE **Remote Indicators & Mounting Accessories** UNIT PRICE IN €



These items are integrated in part VII § DETECTOR ACCESSORIES

Please refer to your specific discount for this chapter to define your price



xx= color type

WH = bright white

IV = ivory

RMK400-xx 1W RECESS MOUNTING KIT
For suspended and drywall ceilings.
For use with standard bases B401/B501.



See § VII
9,30

SMK400-xx 1W SURFACE MOUNTING KIT
Provides for entry of surface wiring conduit.
For use with standard bases B401/B501.



See § VII
7,40

WB1-xx 1W WET BASE SHROUD
Adapter base enclosure for humid environments.
For use with standard bases B401/B501.
Three mounting options are possible: surface mounting, cable mounting and pendant mounting.



See § VII
22,35

▼▼ NEW

IBS-LIDy 4W BASE COVER FOR B501, B501AP, B401 & ABS BASE SOUNDERS PACK OF 10
y= color : W = bright white, DW = detector white (ivory), please specify!!



See § VII
12,75

IRK-2E 1W REMOTE INDICATOR LED
Surface mounted with the supplied mounting box.
Led's will not blink in normal mode on addressable systems !



See § VII
12,75

IRK-E-SI 1W REMOTE INDICATOR LED
Surface mounted with the supplied mounting box.
Led's will not blink in normal mode on addressable systems !



See § VII
13,85

IRK-W-1224 1W LED TECHNOLOGY REMOTE INDICATOR IP55 12-24Vdc
replaces IRK-W-560
Surface mounted



See § VII
75,00



STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem
 Tel. 09-2555333 Fax 09-2555339
 E-mail info@statamat.be
 Web www.statamat.be



by Honeywell

Wireless Detection

REFERENCE	SAGITTARIUS series	UNIT PRICE IN €
-----------	--------------------	--------------------

▼▼ NEW

SAGITTARIUS is a highly advanced wire to wireless system providing a solution for fire detection applications where traditional installations may be unacceptable or uneconomic.

The system is based on a proven protocol and wireless technology derived from the European security industry.

The translator module provides up to 32 wireless fire detectors and devices.

The translator provides for full sensor analogue values, fire and fault information .

The translator is equipped with 3 free programmable relays.

A additional display allows to check the status of the system.

Complies to prEN54:25 on the European Frequency of 868 Mhz.

(LPCB certification ongoing)

All Devices are delivered with batteries.



REFERENCE	Receiver Module	UNIT PRICE IN €
-----------	-----------------	--------------------

▼▼ NEW

SGWE 1W WIRELESS SIGNAL RECEIVER
 locally powered (12-24 Vdc)
 up to 32 wireless devices
 Bi-directional dialogue protocol
 7 transmission channels available (868 MHz)
 3 free programmable relays
 1 monitored output



260,00

▼▼ NEW

SG-PU 1W DISPLAY MODULE WITH KEYPAD
 wireless communication with receiver



310,00







STATAMAT








BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem
Tel. 09-2555333 Fax 09-2555339
E-mail info@statamat.be
Web www.statamat.be

MORLEY IAS
FIRE SYSTEMS

by Honeywell

REFERENCE	Wireless Detectors		UNIT PRICE IN €
▼▼ NEW			
SG100	1W	WIRELESS OPTICAL SMOKE DETECTOR Includes 360° bicolor LED & base	 220,00
▼▼ NEW			
SG200	1W	WIRELESS MULTI-TECH OPTIC / HEAT DETECTOR Includes 360° bicolor LED & base	 220,00
▼▼ NEW			
SG350	1W	WIRELESS HEAT DETECTOR Includes 360° bicolor LED & base	 220,00
DECORLINE			
▼▼ NEW			
/SC	4W	SUPPLEMENT FOR SPECIAL COATED DETECTOR	 57,00

REFERENCE	Wireless Devices		UNIT PRICE IN €
▼▼ NEW			
SGCP100	1W	WIRELESS MANUAL CALL POINT Complies EN54-11 Includes surface mounting box & break glass	 268,00
▼▼ NEW			
SGMI100	1W	WIRELESS MONITORED INPUT MODULE	 198,00
▼▼ NEW			
SGMC100	1W	WIRELESS CONTROL MODULE With relay (needs an external power supply)	 148,00
▼▼ NEW			
SGRS100	1W	WIRELESS SOUNDER MAX 100DB, 3 TONES RED	
SGRS100-NL	1W	AS SGRS100 BUT WITH SLOW WHOOP	
SGWRS100	4W	AS SGRS100 BUT WATER PROOF	
▼▼ NEW			
SGRS100/W	4W	WIRELESS SOUNDER MAX 100DB, 3 TONES WHITE	
SGRS100-NL/W	4W	AS SGRS100/W BUT WITH SLOW WHOOP	
SGWRS100/W	4W	AS SGRS100/W BUT WATER PROOF	
▼▼ NEW			
SGRS100-AV	4W	WIRELESS SOUNDER-FLASH RED	700,00
SGRS100-AV/W	4W	AS SGRS100-AV BUT WHITE	
SGWRS100-AV	4W	AS SGRS100-AV BUT WATER PROOF	
▼▼ NEW			
CR-123	1W	MAIN LITHIUM BATTERY FOR WIRELESS DEVICES Provides approx. 5 years autonomy (1PC/DEVICE)	 5,50
▼▼ NEW			
CR-2032	1W	BACK UP LITHIUM BATTERY FOR WIRELESS DEVICES Provides approx. 6 months added autonomy (1PC/DEVICE)	 2,50

**STATAMAT**

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem







Tel. 09-2555333 Fax 09-2555339

E-mail info@statamat.be

Web www.statamat.be

MORLEY IAS
FIRE SYSTEMS

by Honeywell

REFERENCE	F2100 Series Wireless System Extension		UNIT PRICE IN €
FRM2100	1W COMBINED OPTICAL/THERMAL WIRELESS DETECTOR Mounting base included. Local test button. Powered with 2 x 3V Lithium batteries CR123 (not included) VDS Approved (G204005)		385,00
	x= color R = red B = blue		
FDKM2100x	1W WIRELESS DIN MANUAL CALL POINT RED Back box and break glass included. VDS version. Powered with 1 x Lithium battery set CR4148 (not included) VDS Approved (G204014) x= color: R= Red, B= Blue		385,00
FDKM/EG/x	1W SPARE GLASS FOR FDKM2100 (PACK OF 10)		55,00
FGM2100	1W WIRELESS ADDRESSABLE FIRE DETECTION PANEL Able to control till 32 devices on 2 software groups Internal PSU designed for 1,2Ah battery for backup. 2 Fire relays, 2 Fault relays, 1 reset input, 1 external supply input. Frequency: 434 Mhz & 868 Mhz (20 channels in 434 Mhz & 4 in 868 Mhz) VDS Approved (G204004)		1540,00
MI-D21CMO	1W DOUBLE SUPERVISED INPUT + SINGLE RELAY OUTPUT A standard MI-D21CMO module can be used to connect the wireless system to an addressable loop. This will interface the fire & fault relays of both zones and will also enable you to reset the system remotely. Complete with end of line resistors, plug in screw connections, direct decade address entry and tri-colour LED's complete with built-in isolator.		96,00
CR-123	1W LITHIUM BATTERY FOR FRM2100 WIRELESS DETECTOR (2PCS/DET)		5,50
CR-4148	1W LITHIUM BATTERY SET FOR FDKM2100 WIRELESS DIN MCP (1PC/MCP)		41,00



STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem
Tel. 09-2555333 Fax 09-2555339
E-mail info@statamat.be
Web www.statamat.be

MORLEY IAS
FIRE SYSTEMS

by Honeywell

Addressable Manual Call Points

Addressable Manual Call Points for flush or surface mounting applications.

All products are available in a wide variety of colours.

Standard color is red.

LPCB approved EN54-11



REFERENCE Addr. Call Points for Intelligent Morley-IAS Systems UNIT PRICE IN €

RED



The series red MCP is LPCB approved EN54-11

The RED call points are delivered with the EN54-11 labels:

Operating Element label: EN54-11 'dot & arrows'

Function label: EN54-11 'Burning House'

For other labels, please order specific foil additionally.



MI-MCP-GLASS	1W MANUAL CALL POINT WITH BREAK GLASS	70,50
	Including EN54 break glass, without backbox Compatible with standard electric embeded box with screws	
MI-MCP-GLASS-1	1W MANUAL CALL POINT WITH ISOLATOR & BREAK GLASS	84,50
	Including EN54 break glass & isolator, without backbox Compatible with standard electric embeded box with screws	
MI-MCP-FLEX	1W MANUAL CALL POINT WITH FLEXIBLE	71,50
	Including EN54 flexible element, without backbox Compatible with standard electric embeded box with screws	
MI-MCP-FLEX-1	1W MANUAL CALL POINT WITH ISOLATOR & FLEXIBLE	85,50
	Including EN54 flexible element & isolator, without backbox Compatible with standard electric embeded box with screws	

COLOR VERSION

Note: Replace x by the first letter of the required color

Y = yellow; G= Green; B = Blue;

W = white (lead time 4 weeks)



Standards labels for the NOT RED MCP are:

Operating Element label: EN54-11 'dot & arrows'

Function label: Plain color

For other labels, please order specific foil additionally.



MI-MCP-GLASS-X	1W MANUAL CALL POINT WITH BREAK GLASS	83,50
	Including EN54 break glass, without backbox Compatible with standard electric embeded box with screws	
MI-MCP-GLASS-1-X	1W MANUAL CALL POINT WITH ISOLATOR & BREAK GLASS	93,50
	Including EN54 break glass & isolator, without backbox Compatible with standard electric embeded box with screws	



STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE


Finlandstraat 5A (haven 8000C) 9940 Evergem
 Tel. 09-2555333 Fax 09-2555339
 E-mail info@statamat.be
 Web www.statamat.be

MORLEY IAS
 FIRE SYSTEMS




by Honeywell

MI-MCP-FLEX-X	1W MANUAL CALL POINT WITH FLEXIBLE Including EN54 flexible element, without backbox Compatible with standard electric embeded box with screws	84,50
MI-MCP-FLEX-1-X	1W MANUAL CALL POINT WITH ISOLATOR & FLEXIBLE Including EN54 flexible element & isolator, without backbox Compatible with standard electric embeded box with screws	94,50

REFERENCE	Mounting Boxes for Call Points	UNIT PRICE IN €
-----------	---------------------------------------	--------------------

RED		
SR1T	1W SURFACE MOUNTING BOX RED With 1 termination for screen connection.	 4,75
COLOR VERSION		
Sx1T	1W SURFACE MOUNTING BOX Note: Replace x by the first letter of the required color Y = yellow; G= Green; B = Blue; W = white	6,60

REFERENCE	Manual Call Points WCP Series IP67	UNIT PRICE IN €
-----------	---	--------------------

RED		
		
<p>The RED call points are delivered with the EN54-11 labels: Operating Element label: EN54-11 'dot & arrows' Function label: EN54-11 'Burning House' For other labels, please order specific foil additionally.</p>		
MI-WCP-R/SG	1W MCP SURFACE WITH BREAK GLASS ELEMENT Including backbox and break glass	215,00
MI-WCP-R/SF	1W MCP SURFACE WITH FLEXIBLE ELEMENT Including backbox and flexible operating element	216,00
MI-WCP-R/I/SG	1W MCP SURFACE WITH BREAK GLASS ELEMENT & ISOLATOR Including backbox, break glass and short circuit isolator	225,00
MI-WCP-R/I/SF	1W MCP SURFACE WITH FLEXIBLE ELEMENT & ISOLATOR Including backbox, flexible operating element & short circuit isolator	226,00



STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem
 Tel. 09-2555333 Fax 09-2555339
 E-mail info@statamat.be
 Web www.statamat.be

MORLEY IAS
 FIRE SYSTEMS

by Honeywell

COLOR VERSION



x= color type

Y = yellow

G = green

B = blue

W = white



Standards labels for the NOT RED MCP are:
 Operating Element label: EN54-11 'dot & arrows'
 Function label: Plain color
 For other labels, please order specific foil additionally.



MI-WCP-x/SG	4W MCP SURFACE WITH BREAK GLASS ELEMENT Including backbox and break glass	246,00
MI-WCP-x/SF	4W MCP SURFACE WITH FLEXIBLE ELEMENT Including backbox and flexible operating element	255,00
MI-WCP-x/I/SG	4W MCP SURFACE WITH BREAK GLASS ELEMENT & ISOLATOR Including backbox, break glass and short circuit isolator	247,00
MI-WCP-x/I/SF	4W MCP SURFACE WITH FLEXIBLE ELEMENT & ISOLATOR Including backbox, flexible operating element & short circuit isolator	256,00

REFERENCE Accessories for Manual Call Points UNIT PRICE IN €



These items are integrated in
 part VII § ACCESSORIES FOR MANUAL CALL POINTS &
 in part X SPARE PARTS

KG1 X 10	1W PACK OF 10 SPARE EN54 BREAK GLASS FOR EN54 CALL POINTS	See § X 16,20
PS230	1W PACK OF 10 SPARE EN54 FLEXIBLE OP. ELEMENTS FOR MI CALL POINTS	See § X 20,40
PS200	1W TRANSPARENT PROTECTIVE HINGED COVER	See § VII 4,23
SC070	1W PACK OF 10 SPARE TEST KEYS	See § X 11,54
SC071	1W PACK OF 20 TERMINAL BLOCKS	See § X 81,00
KL1 X 5	1W PACK OF 5 EARTH CONTINUITY LINKS	See § VII 4,80



STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem
Tel. 09-2555333 Fax 09-2555339
E-mail info@statamat.be
Web www.statamat.be

MORLEY IAS
FIRE SYSTEMS

by Honeywell

REFERENCE **Foil of Labels for Call Points & Switches** UNIT PRICE
IN €



These items are integrated in part VII § foil of labels for CALL POINTS & SWITCHES
Please refer to your specific discount for this chapter to define your price



Each foil contains 48 labels

MCP-LABEL F 007	1W	FOIL OF 'PLAIN RED' LABELS		(52,50)
MCP-LABEL F 010	1W	FOIL OF 'BRAND FEU' LABELS (black on red)		(52,50)
MCP-LABEL F 028	1W	FOIL OF 'ALARME INCENDIE' LABELS (black on red)		(52,50)
MCP-LABEL F 056	1W	FOIL OF 'BRAND FEU' LABELS (black on yellow)		(52,50)
MCP-LABEL F 081	1W	FOIL OF 'FEU' LABELS (black on yellow)		(52,50)
MCP-LABEL F 082	1W	FOIL OF 'BLUSKNOP' LABELS (black on yellow)		(52,50)
MCP-LABEL F 141	1W	FOIL OF 'BRAND' LABELS (black on red)		(52,50)
MCP-LABEL F 103	1W	FOIL OF 'GASBLUSSING' LABELS (black on yellow)		(52,50)
MCP-LABEL F 108	1W	FOIL OF 'ALARME EVACUATION' LABELS (white on red)		(52,50)
MCP-LABEL F 120	1W	FOIL OF 'BRAND ALARM' LABELS (black on red)		(52,50)
MCP-LABEL F 138	1W	FOIL OF 'ALERTE INCENDIE' LABELS (black on red)		(52,50)
MCP-LABEL F 141	1W	FOIL OF 'BRAND' LABELS (black on yellow)		(52,50)
MCP-LABEL F 217	1W	FOIL OF 'EXTINCTION' LABELS (black on yellow)		(52,50)
MCP-LABEL F 218	1W	FOIL OF 'RUNNING MAN' LABELS (white on green)		(52,50)
MCP-LABEL F 220	1W	FOIL OF 'BIJ NOOD DEUR OPEN' LABELS (white on blue)		(52,50)
MCP-LABEL F 222	1W	FOIL OF 'EN54 BURNING HOUSE' LABELS (white on red)		(52,50)
MCP-LABEL F 228	1W	FOIL OF 'DEUR ONGRENDELING' LABELS (white on blue)		(52,50)
MCP-LABEL F 235	1W	FOIL OF 'ALERTE WAARSCHUWING' LABELS (black on red)		(52,50)
MCP-LABEL F 244	1W	FOIL OF 'UITSTEL BLUSSING' LABELS (white on blue)		(52,50)



STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem
 Tel. 09-2555333 Fax 09-2555339
 E-mail info@statamat.be
 Web www.statamat.be

MORLEY IAS
 FIRE SYSTEMS

by Honeywell

Analogue Morley IAS Modules

The new family of input/output modules are available in single and multi-way models within the same mechanical package, reducing both the cost of installation and the mounting space required.

Their unique mechanical design allows each module to be mounted in either a wall box, on a DIN rail or within any type of enclosure. Irrespective of the mounting method chosen, the address switch is both visible and accessible for selection.

Each module has built-in short circuit protection for the communications loop; however, to increase application flexibility, the isolators can be selected/deselected on an individual module basis.

To help engineers in the maintenance and fault-finding process, both the LEDs and the switches can be viewed without having to remove the cover of the surface mounting box. The LEDs, being multi-colour, provide diagnostic information regarding the status of each individual input/output.

For ease of installation, testing and maintenance, the field wiring terminals are of plug-in design.

REFERENCE	MI Series Addressable Modules		UNIT PRICE IN €
MI-MM3E	1W	ADDRESSABLE MICRO MONITOR MODULE Supervised monitoring of contact with LED output	60,50
MI-DMMI	1W	SINGLE SUPERVISED INPUT MODULE Complete with end of line resistor, plug in screw connections, direct decade address entry and tri-colour LED's complete with built-in isolator.	64,50
MI-DMM2I	1W	DOUBLE SUPERVISED INPUT MODULE Complete with end of line resistors, plug in screw connections, direct decade address entry and tri-colour LED's complete with built-in isolator.	80,50
MI-DCMO	1W	SINGLE SUPERVISED OUTPUT MODULE Complete with end of line resistor, plug in screw connections, direct decade address entry and tri-colour LED's complete with built-in isolator.	74,50
MI-D21CMO	1W	DOUBLE SUPERVISED INPUT + SINGLE RELAY OUTPUT Complete with end of line resistors, plug in screw connections, direct decade address entry and tri-colour LED's complete with built-in isolator.	96,00
MI-D240CMO	1W	SINGLE 240VAC/5A RELAY MODULE Complete with surface mount box, direct decade address entry and tri-colour LED's complete with built-in isolator.	98,00
MI-D240 CMO-KO	1W	SINGLE 240VAC/5A RELAY MODULE (KNOCK OUTS) Wall mount with knockouts and rubber grommets, direct decade address entry and tri-colour LED's complete with isolator.	100,00







STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE





Finlandstraat 5A (haven 8000C) 9940 Evergem
 Tel. 09-2555333 Fax 09-2555339
 E-mail info@statamat.be
 Web www.statamat.be






by Honeywell

MI-D240 CMO-DIN	1W SINGLE 240VAC/5A RELAY MODULE (DIN RAIL MOUNT.) Complete with DIN mounting enclosure, direct decade address entry and tri-colour LED's complete with built-in isolator.		113,00
MI-DISO	1W SINGLE ISOLATOR MODULE Complete with plug in screw connections and tri-colour LED.		59,00
MI-CZME	1W CONVENTIONAL ZONE INPUT MODULE Complete with end of line resistors, plug in screw connections, direct decade address entry and tri-colour LED's complete with built-in isolator.		139,00
ISO524-1	1W MICRO ISOLATOR MODULE To build inside SR3T back box of analogue call point.		28,35

REFERENCE MI Series Modules Mounting Accessories UNIT PRICE IN €

M200-SMB	1W SURFACE MOUNT BOX To be used with MI series modules.		11,00
M200-SMB KO	1W SURFACE MOUNT BOX WITH KNOCKOUTS Complete with rubber grommets.		12,85
M200-PMB	1W PANEL MOUNTING CLIP With 2 holes for fixing To be used with MI series modules.		7,45
M200-DIN	1W DIN-RAIL MOUNTING CLIP To be used with MI series modules.		7,45

REFERENCE MI Series Addressable Multi-way Modules UNIT PRICE IN €

ISOX-8	1W 8-ISOLATOR MODULE CARD Splits 1 intelligent loop into 4 isolated closed sub-loops Requires external 24VDC power source.		235,00
MMX- 10MH	1W 10 WAY ADDRESSABLE INPUT MONITOR CARD Complete with end of line resistors, individual input disable switches, plug in screw connections and on board LED's LED's with the facility for external LED's. (unboxed)		540,00
CMX- 10RMH	1W 10 WAY ADDRESSABLE RELAY CONTROL CARD Contact rating 30VDC - 1A. Complete with individual output disable switches, plug in screw connections and on board LED's with the facility for external LED's. (unboxed)		595,00







STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE






Finlandstraat 5A (haven 8000C) 9940 Evergem
 Tel. 09-2555333 Fax 09-2555339
 E-mail info@statamat.be
 Web www.statamat.be



by Honeywell

MCX-55MH	1W 5 WAY ADDRESSABLE INPUT MONITOR & 5 WAY ADDRESSABLE RELAY CONTROL CARD Complete with end of line resistors and relais (30VDC - 1A) individual input & output disable switches, plug in screw connections and on board LED's with the facility for external LED's. (unboxed)		580,00
▼▼ NEW			
MI-CR-6	2W 6 WAY RELAY MULTIMODULE CPD certified		405,00
▼▼ NEW			
MI-CZ-6	2W 6 WAY ZONE INTERFACE MULTIMODULE CPD certified		415,00
▼▼ NEW			
MI-SC-6	2W 6 WAY SUPERVISED SOUNDERS OUTPUTS MULTI-MODULE CPD certified		495,00

REFERENCE	Module Mounting Accessories	UNIT PRICE IN €
-----------	-----------------------------	--------------------

SMB6-VO	1W MULTI-MOUNT ABS ANTISTATIC BOX VO Flame retardant box in Notifier grey colour Compatible with MI-MMX-10MH, MI-CMX-10RMH & MI-MCX-55MH Can hold up to 6 MI series modules (DIN rail mounting clip not required). Dimensions: 245 x 180 x 50 mm		55,00
▼▼ NEW			
SMBW-VO	1W ABS ANTISTATIC BOX FOR xx-6 OR im-10 MULTIMODULE VO Flame retardant box, color cream Can hold 1 multimodule (MI-CMX-10RM, MI-MMX-10M, MI-MCX-55M or MI-xx-6) Dimensions: (w)245 x (h)180 x (d)50 mm		55,00
▼▼ NEW			
BB-2	1W MULTI-MOUNT STEEL CABINET Up to 2 modules (MI-xx-6 series) Red coated enclosure		125,00
▼▼ NEW			
BB-6	1W MULTI-MOUNT CABINET Up to 6 modules (MI-xx-6 series) Red coated enclosure		235,00
▼▼ NEW			
CH-6	1W MOUNT CHASSIS FOR BB-6 The CH-6 chassis is mounted in the BB-6 cabinet. It is shipped with two self-threading screws, which are used to fasten the chassis to the back wall of the cabinet.		67,50



STATAMAT



BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE






Finlandstraat 5A (haven 8000C) 9940 Evergem
Tel. 09-2555333 Fax 09-2555339
E-mail info@statamat.be
Web www.statamat.be

MORLEY IAS
FIRE SYSTEMS

by Honeywell

Analogue Duct Detectors

REFERENCE	DHX500 Series	UNIT PRICE IN €
DHX-502	<p>1W DUCT DETECTOR HOUSING Operation range: 15 to 32VDC This version contains no relays. Air velocity rating from 2,5 m/s to 20 m/s Connections for remote LED output, remote test station, remote annunciator The duct detector samples air passing through a duct and gives dependable performance for shutdown of fans, blowers or air co systems, so preventing the spread of toxic smoke and fire gases through the protected area. To be ordered separately: Detector & ST-xx Inlet Sampling Tube</p>	 142,50
DHX-501	<p>1W DUCT DETECTOR HOUSING WITH ELECTRONIC PCB 24VDC or 24VAC operation Air velocity rating from 2,5 m/s to 20 m/s Equipped with DPDT Auxiliary Relay Contacts Sounder output, remote LED output, remote test station, remote annunciator Can be used as a part of fire detection system. Can be used to activate a local sounder and shutdown fans, blowers or air co systems, so preventing the spread of toxic smoke and fire gases through the protected area. To be ordered separately: Detector & ST-xx Inlet Sampling Tube</p>	 230,00

REFERENCE	Accessories	UNIT PRICE IN €
	<p> These items are integrated in part VII § Duct Detector Accessories & part X § X Spare Parts</p>	
ST-1.5	<p>1W INLET SAMPLING TUBE (LENGTH=457 MM)</p>	 See § VII 9,70
ST-3	<p>1W INLET SAMPLING TUBE (LENGTH=916 MM)</p>	 See § VII 12,25
ST-5	<p>1W INLET SAMPLING TUBE (LENGTH=1520 MM)</p>	 See § VII 16,85
ST-10	<p>1W INLET SAMPLING TUBE (LENGTH=3255 MM)</p>	 See § VII 30,50
F-36-05-00	<p>3W REPLACEMENT FILTER FOR DUCT DETECTORS</p>	See § X 6,10
P-48-21-00	<p>3W TUBE END PLUG FOR DUCT DETECTOR</p>	See § X on request
A-2650-01	<p>3W COMPLETE INSTALLATION KIT FOR DUCT DETECTOR</p>	See § X on request



STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem
Tel. 09-2555333 Fax 09-2555339
E-mail info@statamat.be
Web www.statamat.be

MORLEY IAS
FIRE SYSTEMS

by Honeywell

Analogue Beam Detectors


The **MI-LPB2** is an addr. analogue reflectortype linear optical beam detector designed to operate as a component of an analogue Morley-IAS fire system.

The **MI-LPB2 beam** detector is a loop powered combined transmitter/receiver unit that can be directly connected to an analogue Morley-IAS loop.

Alignment of the detector is easy with the aid of the detector's "gunsight" targeting device and can be "fine tuned" with the aid of a numerical signal strength indicator.

The detector incorporates automatic drift compensation, whereby the detector will adjust its detection thresholds in line with any long term signal reduction of the beam caused by contamination of the optical surface.

LPC&VdS Approved EN54-12:2002

REFERENCE	MI-LPB2 Series	UNIT PRICE IN €
MI-LPB2	1w ADDR. REFLECTIVE IR BEAM DETECTOR Infrared operation. Short range reflector (5M-75M) included. Loop powered, direct decade address entry. Voltage Range: 15 to 32 Vdc; IP54 Standby Current: 2mA, Alarm Current: 8mA Detector Dimension: 254mm x 190mm x 84mm Reflector Dimension: 200mm x 230mm	 820,00









STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem
Tel. 09-2555333 Fax 09-2555339
E-mail info@statamat.be
Web www.statamat.be

MORLEY IAS
FIRE SYSTEMS

by Honeywell

REFERENCE	MI-LPB2 Accessories		UNIT PRICE IN €
		These items are integrated in part VII § ACCESSORIES FOR BEAM DETECTORS Please refer to your specific discount for this chapter to define your price	
BEAM-LRK	1W	LONG-RANGE REFLECTOR (75M-100M) 3 reflectors with the following dimensions each: Reflector Dimension: 200mm x 230mm	 See §VII 235,00
BEAM-SMK	1W	SURFACE MOUNTING BOX Absolutly needed in combination with the mounting Bracket kit	 See §VII 29,60
BEAM-MMK	1W	MOUNTING BRACKET - SWIVEL TYPE	 See §VII 165,00
BEAM-HK	1W	HEATER KIT FOR 6500R To avoid condensation problems when used in non heated rooms.	 See §VII 126,50
BEAM-HKR	1W	HEATER KIT FOR REFLECTOR To avoid condensation problems when used in non heated rooms.	 See §VII 272,50
▼ ▼ NEW			See §VII
6500-RTS-KEY	1W	REMOTE TEST KEY SWITCH	103,00



STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem
Tel. 09-2555333 Fax 09-2555339
E-mail info@statamat.be
Web www.statamat.be

MORLEY IAS
FIRE SYSTEMS

by Honeywell

Aspiration Systems

REFERENCE	A300 series	UNIT PRICE IN €
-----------	-------------	--------------------

The A300 series Aspirating Detectors is designed for the instances where the high sensitivity that is normally inherent in Aspiration detectors is an unnecessary expense or nuisance due to false alarms. The A300 series aspiration detectors become an integral part of the main fire detection system with direct communication from the panel to the installed detectors.

* Plastic housing (IP65 optional)

* Supply voltage 18-30VDC -

Includes:

- One or two Fault relays (depend type)

VdS Approved EN54-20 (G206067)

Order Laser Detector MI-LZR & base B501AP separately!



A310E

1W ASPIRATING SYSTEM SINGLE CHANNEL (MAX 100M)

VdS Approved (G206067)

Supply voltage 18-30VDC - Plastic housing (IP65 optional)

Two B501 bases included. One or two Pinnacles detectors optional.

One Fault relays included

Max. sampling pipe length 100m

1 Sampling Air Inlet Ø25 mm



1595,00

A320E

1W ASPIRATING SYSTEM 2 CHANNELS (MAX 200M)

VdS Approved (G206067)

Supply voltage 18-30VDC - Plastic housing (IP65 optional)

Two B501 bases included. Two Pinnacle detectors optional (1/channel)

Two Fault relays included

Max. sampling pipe length 100m per channel

2 Sampling Air Inlets Ø25 mm



1975,00

REFERENCE	Sampling Pipes, Fittings & Accessories	UNIT PRICE IN €
-----------	--	--------------------

02-FLU2

4W EXTERNAL FILTER FOR VERY HARSH ENVIRONMENT


Horizontal mounting, 2 inlets 25mm



546,00

02-WT-01

**4W EXTERNAL WATER TRAP KIT
traps the water co**



300,00













STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem
Tel. 09-2555333 Fax 09-2555339
E-mail info@statamat.be
Web www.statamat.be

MORLEY IAS
FIRE SYSTEMS

by Honeywell

02-WT-HEAT-01	4W EXTERNAL WATER TRAP HEATER KIT Heats the air flow		975,00
PFIL-EXT	6W EXTERNAL FILTER FOR VERY HARSH ENVIRONMENT Vertical mounting		399,00
ABS 010	WARNING LABELS FOR CAPILARY SAMPLING POINT ROLL OF 100 PIECES		30,30
ABS 011	1W CEMENT 250ml		21,20
ABS 001/25	1W 90° SWEEPING BEND DIAMETER 25MM RED PACK OF 10		102,00
ABS 001/25-WH	2W WHITE VERSION OF ABS 001/25 PACK OF 10		111,00
ABS 002/25	1W 45° SWEEPING BEND DIAMETER 25MM PACK OF 10		47,40
ABS 002/25-WH	2W WHITE VERSION OF ABS 002/25 PACK OF 10		50,00
ABS 003/25	1W SOCKET UNION DIAMETER 25 MM PACK OF 10		135,50
ABS 003/25-WH	2W WHITE VERSION OF ABS 003/25 PACK OF 10		146,00
ABS 004	1W PIPE CLIPS - RED PACK OF 10		16,10
ABS 004-WH	1W WHITE VERSION OF ABS 004 PACK OF 10		17,50
ABS 005/25	1W JOINTING SOCKET DIAMETER 25 MM PACK OF 10		22,70
ABS 005/25-WH	2W WHITE VERSION OF ABS 005/25 PACK OF 10		24,15
ABS 005/1	1W 25MM TO 27MM ADAPTER PACK OF 10		22,70
ABS 005/1-WH	2W WHITE VERSION OF ABS 005-1 PACK OF 10		111,00
ABS 006/25	1W T' PIECE DIAMETER 25MM PACK OF 10		121,00
ABS 006/25-WH	2W WHITE VERSION OF ABS 006/25 PACK OF 10		131,00





STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem
Tel. 09-2555333 Fax 09-2555339
E-mail info@statamat.be
Web www.statamat.be

MORLEY IAS
FIRE SYSTEMS

by Honeywell

ABS 007/25	1W	END CAP DIAMETER 25MM PACK OF 10		22,70
ABS 007 /25-WH	2W	WHITE VERSION OF ABS 007/25 PACK OF 10		24,15
ABS 008/25	1W	PIPE DIAMETER 25 MM - 3 METRES LONG PACK OF 10		158,00
ABS 008 /25-WH	2W	WHITE VERSION OF ABS 008/25 PACK OF 10		171,50



STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE




Finlandstraat 5A (haven 8000C) 9940 Evergem
 Tel. 09-2555333 Fax 09-2555339
 E-mail info@statamat.be
 Web www.statamat.be

MORLEY IAS
 FIRE SYSTEMS

by Honeywell

REFERENCE **Remote Sampling Point Assemblies** UNIT PRICE
 IN €



ABS 019C /25	1W	CAPILLARY SAMPLING POINT- CONICAL HEAD TO CONNECT ON A ABS 008/25 PIPE Includes T-piece, 2 mtrs capillary tube & sampling point		41,50
ABS 019C /25-WH	2W	WHITE VERSION OF ABS 019C/25		45,00
ABS 019F/25	1W	CAPILLARY SAMPLING POINT-FLUSH DISC TO CONNECT ON A ABS 008/25 PIPE Includes T-piece, 2 mtrs capillary tube & sampling point		41,50
ABS 019F /25-WH	2W	WHITE VERSION OF ABS 019F/25		45,00
ABS 020/25	1W	CAPILLARY SAMPLING POINT- DISCRETE SAMPLING POINT 8MM TO CONNECT ON A ABS 008/25 PIPE Includes T-piece, 2 mtrs capillary tube & sampling point		36,00
ABS 020 /25-WH	2W	WHITE VERSION OF ABS 020/25		39,50
ABS 019C /25EC	1W	CAPILLARY <u>END CAP</u> SAMPLING POINT- CONICAL HEAD TO CONNECT ON A ABS 008/25 PIPE Includes <u>end cap</u> reduction, 2 mtrs capillary tube & sampling point		36,00
ABS 019C /25EC-WH	2W	WHITE VERSION OF ABS 019C/25EC		39,50
ABS 019F /25EC	1W	CAPILLARY <u>END CAP</u> SAMPLING POINT-FLUSH DISC TO CONNECT ON A ABS 008/25 PIPE Includes <u>end cap</u> T-piece, 2 mtrs capillary tube & sampling point		36,00
ABS 019F /25EC-WH	2W	WHITE VERSION OF ABS 019F/25EC		39,50
ABS 020 /25EC	1W	CAPILLARY <u>END CAP</u> SAMPLING POINT- DISCRETE SAMPLING POINT 8MM TO CONNECT ON A ABS 008/25 PIPE Includes <u>end cap</u> T-piece, 2 mtrs capillary tube & sampling point		30,30
ABS 020 /25EC-WH	2W	WHITE VERSION OF ABS 020/25EC		34,00






STATAMAT

BRANDPREVENTIE - BRANDBESTRIJDING - DETECTIE

Finlandstraat 5A (haven 8000C) 9940 Evergem
Tel. 09-2555333 Fax 09-2555339
E-mail info@statamat.be
Web www.statamat.be

MORLEY IAS
FIRE SYSTEMS

by Honeywell

REFERENCE	Components		UNIT PRICE IN €
CAP-RED	1w	10mm NYLON TUBE - RED (per metre)	 4,20
CAP-WHITE	1w	10mm NYLON TUBE - WHITE (per metre)	5,00
ABS 021/25	1w	CAPILLARY END CAP FOR ABS 008/25 PIPE Reduces 25 m pipe to 10mm pipe	 16,50
ABS 021 /25-WH	2w	WHITE VERSION OF ABS 021/25	20,00
ABS 022/25	1w	CAPILLARY T PIECE FOR ABS 008/25 PIPE Reduces 25 mm pipe to 10mm pipe	 24,85
ABS 022 /25-WH	2w	WHITE VERSION OF ABS 022/25	27,50